s.

CLAIMS

- 1.-7. (canceled)
- 8. (currently amended) <u>A malatyl polysaccharide</u> Malatyl polysaccharides prepared by reacting <u>at a pH of 9-13</u> polysaccharides and an epoxy compound selected from the group consisting of cis-epoxy succinate or <u>and</u> epoxy carboxylic acids, <u>wherein carboxyl groups of the epoxy compound are preserved in the malatyl polysaccharide</u>.
- 9. (currently amended) [A] <u>The</u> malatyl polysaccharide according to claim 8 in the form of malatyl starch of the general formula (I)[:].

10. (currently amended) [A] <u>The</u> malatyl polysaccharide according to claim 8 in the form of malatyl galactomannan of the general formula (IIa).

11. (currently amended) [A] <u>The</u> malatyl polysaccharide according to claim 8 in the form of malatyl galactomannan of the general formula (IIb).

12/1/03: Amd for Ser. No. 09/889,368 - Inventor(s): W. Lazik. - Filing Date: 7/12/2001

s.


03/06

12. (currently amended) [A] The malatyl polysaccharide according to claim 8 in the form of malatyl galactomannan of th general formula (IIa) and (IIb).

lla.

and ΠР

(currently amended) [A] The malatyl polysaccharide according to claim 8 in the form of malatyl cellulose of the general formula (III)_



14. (currently amended) A method of preparing malatyl polysaccharides according to claim 8 4, comprising the step of:

reacting polysaccharides at a pH of 9-13 with an epoxy compound selected from the group consisting of cis-epoxy succinate and or analog epoxy carboxylic acids, wherein the carboxyl groups of the epoxy compound are preserved in the malatyl polysaccharide.

- 15. (currently amended) [A] The method according to claim 14, wherein the epoxy compound is epoxy succinate and the step of reacting is carried out in a suspension.
- 16. (currently amended) [A] The method according to claim 14, wherein the epoxy compound is epoxy succinate and the step of reacting is carried out in solid phase.
 - 17. (canceled)